

SAFETY DATA SHEET "CRUSHED CONCRETE"

Section 1: PRODUCT AND COMPANY INFORMATION

Product Name(s): CONSOLIDATED MATERIALS CRUSHED CONCRETE

Product Identifiers: Crushed Concrete, Recycled Concrete, Crushed Concrete Base Course, Recycled Concrete Base Course, Reclaimed Concrete Material (RCM), Recycled Concrete Pavement (RCP).

Manufacturer	Information Telephone Number	EMERGENCY PHONE NUMBER
Consolidated Materials, Inc.	847-658-4342 7AM-5PM STD	1-800-451-8346 (3E HOTLINE)
1320 S. Virginia Road Crystal Lake IL, 60014		911 LOCAL

Product Use: Crushed concrete is used as an aggregate in concrete or asphalt bases, concrete or asphalt mixes, flowable fill, as bulk fill material and other construction applications.

Note: This MSDS covers many concrete products. Individual composition of hazardous constituents will vary between types of crushed concrete.

Section 2: COMPOSITION/INFORMATION ON INGREDIENTS





Component	Percent (By Weight)	CAS Number	OSHA PEL -TWA (mg/m ³)	ACGIH TLV-TWA (mg/m ³)	LD ₅₀ (mouse, oral)	LC ₅₀
Crystalline Silica	0-90	14808-60-7	[(10) / (%SiO ₂ +2)] (R); [(30) / (%SiO ₂ +2)] (T)	0.025 (R)	NA	NA
Calcium Hydroxide	15-25	1305-62-0	15 (T); 5 (R)	5 (T)	7300 mg/kg	NA
Portland Cement*	0-10	65997-15-1	15 (T); 5 (R)	1 (R)	NA	NA
Particulate Not Otherwise Regulated	-	NA	15 (T); 5 (R)	10 (T); 3 (R)	NA	NA

Note: Exposure limits for components noted with an * contain no asbestos and <1% crystalline silica

Concrete is a mixture of gravel or rock, sand, Portland cement and water. It may also contain fly ash, slag, silica fume, calcined clay, fibers (metallic or organic) and color pigment. Properties and composition of crushed concrete can vary depending on the original properties and composition of the recovered concrete.

Concrete contains cement which is made from materials mined from the earth and is processed using energy provided by fuels. Trace amounts of chemicals may be detected during chemical analysis. For example, cement may contain trace amounts of calcium oxide (also known as free lime or quick lime), free magnesium oxide, potassium and sodium sulfate compounds, chromium compounds, nickel compounds, and other trace compounds.

Section 3: HAZARD IDENTIFICATION

	WARNING	 Respiratory Protection  Eye Protection  Gloves
	<p>Toxic - Harmful by inhalation. (Contains crystalline silica)</p> <p>Use proper engineering controls, work practices, and personal protective equipment to prevent exposure to wet or dry product.</p> <p>Read MSDS for details.</p>	

SAFETY DATA SHEET "CRUSHED CONCRETE"

Section 3: HAZARD IDENTIFICATION (continued)

Emergency Overview: Crushed concrete varies in size, shape and color, depending on final use. They are not combustible or explosive. A single, short-term exposure to concrete dust presents little or no hazard.

Potential Health Effects:

Eye Contact: Airborne dust may cause immediate or delayed irritation or inflammation. Eye contact with large amounts of concrete dust can cause moderate eye irritation and abrasion. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye.

Skin Contact: Concrete dust may cause dry skin, discomfort, irritation and dermatitis.

Dermatitis: Concrete dust, in association with sweat and friction, can lead to skin irritation and dermatitis. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of concrete dust such as abrasion.

Inhalation (acute): Breathing dust may cause nose, throat or lung irritation, including choking, depending on the degree of exposure.

Inhalation (chronic): Risk of injury depends on duration and level of exposure.

Silicosis: This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a seriously disabling and fatal lung disease. See Note to Physicians in Section 4 for further information.

Carcinogenicity: Concrete is not listed as a carcinogen by IARC or NTP; however, concrete contains trace amounts of crystalline silica which is classified by IARC and NTP as known human carcinogens.

Autoimmune Disease: Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys.

Tuberculosis: Silicosis increases the risk of tuberculosis.

Renal Disease: Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica.

Ingestion: Do not ingest concrete. Although ingestion of small quantities of concrete is not known to be harmful, large quantities can cause distress to the digestive tract.

Medical Conditions Aggravated by Exposure: Individuals with lung disease (e.g. bronchitis, emphysema, COPD, pulmonary disease) can be aggravated by exposure.

SAFETY DATA SHEET "CRUSHED CONCRETE"

Section 4: FIRST AID MEASURES

- Eye Contact:** Rinse eyes thoroughly with water for at least 15 minutes, including under lids, to remove all particles. Seek medical attention for abrasions and burns.
- Skin Contact:** Wash with cool water and a pH neutral soap or a mild skin detergent. Seek medical attention for rash, irritation, dermatitis.
- Inhalation:** Move person to fresh air. Seek medical attention for discomfort or if coughing or other symptoms do not subside.
- Ingestion:** Do not induce vomiting. If conscious, have person drink plenty of water. Seek medical attention or contact poison control center immediately.

- Note to Physician:** The three types of silicosis include:
- Simple chronic silicosis – which results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).
 - Accelerated silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.
 - Acute silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

Progressive massive fibrosis may occur in simple or accelerated silicosis, but is more common in the accelerated form. Progressive massive fibrosis results from severe scarring and leads to the destruction of normal lung structures.

Section 5: FIREFIGHTING MEASURES

- | | | | |
|---------------------------------|---|--------------------------------|---|
| Flashpoint & Method: | Non-combustible | Firefighting Equipment: | Crushed concrete does not pose a fire-related hazard. |
| General Hazard: | Avoid breathing dust. | | A SCBA is recommended to limit exposures to combustion products when fighting any fire. |
| Extinguishing Media: | Use extinguishing media appropriate for surrounding fire. | Combustion Products: | None. |

Section 6: ACCIDENTAL RELEASE MEASURES

- General:** Place spilled material into a container. Avoid actions that cause the concrete dust to become airborne. Avoid inhalation of concrete dust. Wear appropriate protective equipment as described in Section 8.
- Waste Disposal Method:** Dispose of crushed concrete according to Federal, State, Provincial and Local regulations.

SAFETY DATA SHEET "CRUSHED CONCRETE"

Section 16: OTHER INFORMATION

Abbreviations:

>	Greater than	NA	Not Applicable
ACGIH	American Conference of Governmental Industrial Hygienists	NFPA	National Fire Protection Association
CAS No	Chemical Abstract Service number	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act	NTP	National Toxicology Program
CFR	Code for Federal Regulations	OSHA	Occupational Safety and Health Administration
CL	Ceiling Limit	PEL	Permissible Exposure Limit
DOT	U.S. Department of Transportation	pH	Negative log of hydrogen ion
EST	Eastern Standard Time	PPE	Personal Protective Equipment
HEPA	High-Efficiency Particulate Air	R	Respirable Particulate
HMIS	Hazardous Materials Identification System	RCRA	Resource Conservation and Recovery Act
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act
LC ₅₀	Lethal Concentration	T	Total Particulate
LD ₅₀	Lethal Dose	TDG	Transportation of Dangerous Goods
mg/m ³	Milligrams per cubic meter	TLV	Threshold Limit Value
MSHA	Mine Safety and Health Administration	TWA	Time Weighted Average (8 hour)
		WHMIS	Workplace Hazardous Materials Information System

This SDS (Sections 1-16) was revised March 1, 2015

**Copies of this SDS is available at: Consolidated Materials, Inc. 1320 S. Virginia Road Crystal Lake IL, 60014
PH: 847-658-4342**

Consolidated Materials, Inc. (CMI) believes the information contained herein is accurate; **CMI** makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial and State regulations.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.